

Spindle Holder

DR-L spindle integration (horizontal mounting)



- Small size, large through-hole
- High precision, spindle rotation accuracy within 0.005mm
- High speed, maximum speed 3500 rpm.
- Large through-hole, maximum through-hole 46mm
- Synchronous wheel/gear transmission, connected to the motor driven rotation, convenient and simple
- Can be matched with different chucks, used in various high-precision machining fields.



Spindle Holder

Item	DR-25-L	DR-45-L
A	200	240
B	220	260
C	26	46
D	170	210
E	15	15
F	8	8
G	18	18
H	110	135
I	40	60
J	26	26
K	75.5	81
L	16	18
M	44	44
N	196	236
O	25	25
Mounting hole	φ11*4	φ11*4
Through hole	26mm	46mm
Max rotary speed	3500rpm/min	3000rpm/min
Precision	0.005mm	0.005mm
Synchronous spindle	5M-50 tooth Inner40	8M-50 tooth Inner60
Synchronous motor	5M-50 tooth custom-made	8M-25 tooth custom-made
Gear spindle	/	2.5M-90 tooth Inner60
Gear motor	/	2.5M-40 tooth custom-made
Keyway	L22*W6*D3	L22*W6*D3
N.W	24.8kgs	42.6kgs

Specification:

